




PLOMO ÁCIDO ABIERTO

TIPO	V	LEU'S	MIN. CAP. RESERV.		CAPACIDAD AH.			MEDIDAS (MMS)			PESO / KGS	PVP REC. SIN IVA	FOTOS PRODUCTOS
			25 A	75 A	5 H	20 H	100 H	L	A	H			
BATERÍAS 6 VOLTIOS													
TE-35	6		500	135	200	245	272	224	191	276	31	301	
T-605	6	383	383	105	175	210	233	264	181	284	26	248	
T-105	6	438	447	115	185	225	250	264	181	284	28	274	
T-125	6	492	488	132	195	240	266	264	181	284	30	323	
T-145	6	673	530	145	215	260	286	264	181	292	33	409	
J-250P	6	650	540	135	215	250	275	295	178	292	33	425	
J-305G	6	686	620	170	255	310	344	295	178	365	41	495	
J-305P	6	727	675	175	270	315	350	295	178	365	44	549	
J-305H	6	807	745	195	285	335	372	295	178	365	44	624	
L-16G	6	933	750	185	305	370	411	295	178	432	48	603	
L-16P	6	1.004	805	200	320	390	433	295	178	425	51	651	
L-16H	6	1.148	885	225	345	420	466	295	178	425	55	732	

TIPO	V	LEU'S	MIN. CAP. RESERV.		CCA -18°C	CAPACIDAD AH.			MEDIDAS (MMS)			PESO / KGS	PVP REC. SIN IVA
			25 A	75 A		5 H	20 H	100 H	L	A	H		
BATERÍAS 8 VOLTIOS													
T-875	8	438	295	117*	145	170	189	264	181	276	29	274	
T-890	8	511	340	132*	155	190	211	264	181	276	31	355	

TIPO	V	LEU'S	MIN. CAP. RESERV.		CCA -18°C	CAPACIDAD AH.			MEDIDAS (MMS)			PESO / KGS	PVP REC. SIN IVA	
			25 A	75 A		5 H	20 H	100 H	L	A	H			
BATERÍAS 12 VOLTIOS														
24. TMX	12	233	140	36	440	70	85	90	286	171	248	21	258	
27. TMX	12	280	175	45	530	85	105	115	324	171	248	25	280	
27. TMH	12	326	200	51	620	95	115	130	324	171	248	27	318	
J. 150	12		290	70		125	150	166	351	178	276	38	447	
T- 1275	12		290	102*		125	150	166	327	178	276	38	447	
30. XHS	12	373	225	57	665	105	130	145	355	171	238	30	371	
J. 185.P	12	807	375	95		160	195	216	381	178	371	51	608	
J.185.H	12		415	110		180	215		381	178	371	55	676	

TIPO	V	MINU. CAP. RESERVA 25 A	CCA -18°C	CAPACIDAD AH.			MEDIDAS (MMS)			PESO / KGS	PVP REC. SIN IVA	
				5 H	20 H	100 H	L	A	H			
HERMÉTICAS - CICLOS PROFUNDOS												
24 - GEL	12	130	330	60	70	78	276	171	236	24	328	
27 - GEL	12	160	395	72	84	93	324	171	234	29	399	
31 - GEL	12	180	445	80	93	103	329	171	245	31	418	
6V - GEL	6	350	575	143	175	194	260	181	276	31	426	

TIPO	V	MINUTOS CAPACIDAD RESERVA 25 A	CCA -18°C	CAPACIDAD AH.			MEDIDAS (MMS)			PESO / KGS	PVP REC. SIN IVA	
				5 H	20 H	100 H	L	A	H			
HERMÉTICAS - ARRANQUE + CICLOS												
24- AGM	12	130	440	61	80	89	259	168	226	24	312	
27-AGM	12	175	560	76	100	111	305	168	233	30	361	
31-AGM	12	190	720	83	110	122	332	174	221	32	441	
4D-AGM	12	325	1.110	131	165	183	530	209	237	52	667	
8D-AGM	12	460	1.450	179	230	255	521	269	226	70	840	
6V-AGM	6	380	1.100	154	200	222	260	179	270	29	431	

(*) - Capacidad minutos de reserva con descarga de 56A .

www.trojanbattery.com